



- Reliable structure, static loading capacity: 1500KG
- Adjustable feet and castors options are available
- Baying cabinets together easily
- Double mesh front door & rear door, steel rear door
- Top and bottom cable entries
- Front door, rear door and side panel can be easily removed
- Front & rear door with spring lock
- Optional accessories



Model (Size): 2760ST-E (600Wx1000Dx1405Hmm)

Door (Front / Back): Mesh Double / Mesh Double

General

| | |
|----------|---|
| Standard | Comply with ANSI/EIA, RS-310-D; IEC297-2; DIN41491: PART 1; DIN41491: PART 7; GB/T3047.2-92 standard Compatible with 19" international standard, metric system and ETSI standard |
|----------|---|

| | |
|-------------------------|--------|
| Static loading capacity | 1500KG |
|-------------------------|--------|

| | |
|-------------|----------------|
| Cable entry | Top and bottom |
|-------------|----------------|

| | |
|-----------|------------------------------------|
| Door Lock | Front & rear door with spring lock |
|-----------|------------------------------------|

Materials

| | |
|-------|-------------------------------|
| Panel | SPCC cold rolling steel plate |
|-------|-------------------------------|

| | |
|----------------------------|-------|
| Mounting profile thickness | 2.0mm |
|----------------------------|-------|

| | |
|------------------------|-------|
| Others panel thickness | 1.2mm |
|------------------------|-------|