## 47U ST-E Series 47U Server Cabinet



E

- Reliable structure, static loading capacity: 1500KG
- Adjustable feet and castors options are available
- Baying cabinets together easily
- Double mesh front door & rear door, steel rear door
- Top and bottom cable entries
- Front door, rear door and side panel can be easily removed
- Front & rear door with spring lock
- Optional accessories

Model (Size): 4780ST-E (800Wx1000Dx2280Hmm)

Door (Front / Back): Mesh Double / Mesh Double

## General

Standard	Comply with ANSI/EIA, RS-310-D; IEC297-2; DIN41491: PART 1; DIN41491: PART 7; GB/T3047.2-92 standard 7; GB/T3047.2-92 standard Compatible with 19" international standard, metric system and ETSI standard
Static loading capacity	1500KG
Cable entry	Top and bottom
Door Lock	Front & rear door with spring lock

Update Date: February 27, 2025

Specification subject to change without notice

EIGHT LIMITEDNo.18, 4/F., Thriving Industrial Centre, 26-38 Sha Tsui Road, Tsuen Wan, Hong KongTEL: (852) 2413 2222FAX: (852) 2411 3000EMAIL: info@eightgroup.com





## **Materials**

Panel	SPCC cold rolling steel plate
Mounting profile thickness	2.0mm
Others panel thickness	1.2mm

Update Date: February 27, 2025

**EIGHT LIMITED** No.18, 4/F., Thriving Industrial Centre, 26-38 Sha Tsui Road, Tsuen Wan, Hong Kong TEL: (852) 2413 2222 FAX: (852) 2411 3000 EMAIL: info@eightgroup.com