



Features

- Meet DVB-S/S2, MPEG2 and MPEG4
- QPSK demodulation tune, low threshold
- Enhanced OSD (On Screen Display) screen
- Stores up to 2000 channel data
- Adjustable volume and each program can have its own setting
- Power-off memory
- HD picture, high fidelity digital stereo output and SAP Support
- Signal strength display for convenient dish installation and/or adjustment
- Teletext, DiSEqC, 13/18V power control function

Specifications

Model		2000EIG
DVB-S/S2	Tuner Input	DVB-S/S2
	Tuner Input Type	1 x F type female for Input, 1 x F type female for loop through output
	Demodulation	QPSK /8PSK
	Frequency Range	950~2150MHz
	Input Impedance	75 Ω
	InputLevel	-25~ 65 dBuV
	Roll-off Factor	DVB-S:0.35, DVB-S2:0.2,0.25,0.35
	FEC Code Rate	DVB-S QPSK 1/2, 2/3, 3/4, 5/6, 7/8 DVB-S2 QPSK 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 DVB-S2 8PSK 3/5, 2/3, 3/4, 5/6, 8/9, 9/10
	LNB Polarity Selection Voltage	0, 13V, 18V selectable
	LNB Band Selection Tone	0/22 KHz selectable
Audio	Satellite Selection Command	DiSEqC 1.0
	Standard	MPEG 1 Layers 1, 2 (mono, dual channel, and stereo); MPEG-2 AAC-LC & MPEG4, DRA
	Sampling Rate	32, 44.1, 48KHz
Video	Audio Output	Mono, dual mono, stereo, joint stereo
	Standards	MPEG-2 MP@ML for SD, MPEG-2 MP@HL for HD, H.264/AVC MP@L3.0 for SD, HP@L4.1 for HD VC-1 AP@L1 for SD, AP@L3 for HD, AVS+
	Frame Frequency	25 / 50Hz
	Resolution	Up to 1920 x 1080p(60Hz)
	Bit Rate	MPEG-2 MP@ML: 2~15 M bps, MPEG-2 MP@HL: <19 M bps, MPEG-4 AVC HP@L3:<10 M bps MPEG-4 AVC HP@L4: <20 M bps
Interface	Aspect Ratio	4:3 and 16:9
	Video Output	CVBS RCA x 2
	Audio Output	2 pairs of RCA stereo (Audio Left/Audio Right)
General	HDMI	HDMI x 1, HDCP 1.4
	Power Supply	AC 90~256V 50Hz~60Hz 25W
	Power Consumption	Max 25W
	Temperature	Work Temperature: 5~45°C, Storage Temperature: -10~65°C
	Humidity	20~90%, non-condensed
	Dimension	483mm x 270mm x 45mm
	Weight	2.5Kg

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.