



Features

- Standard user interface, be made of high impact plastic
- Easy operation and maintenance
- Can accommodate 1x8 or 1x4 PLC splitter
- Anti-UV, Ultra Violet resistant and rainfall resistant
- Wall and pole mountable
- 2 inlet ports, 2 outlet ports for ordinary cable or drop cable

Specifications

Model		FTMB-ABS-XXD Series
For Number of Couplers		Up to 24
Dimension	Outer	Outer: 380 x 305 x 130 mm
	Inner	Inner: 360 x 250 x 100 mm
Max Capacity	LC	24 Capacity / 48 cores (Max.)
	SC	24 Capacity / 24 cores (Max.)
	ST	24 Capacity / 24 cores (Max.)
	FC	24 Capacity / 24 cores (Max.)
Operating Temperature		-40 °C ~ + 55 °C
Atmospheric Pressure		62 Kpa ~ 106 kpa
Material		ABS
Installation		Wall-mounting or pole-mounting
Application		Local Area Network, CATV Network, FTTx System, Wide Area Network, Test Instruments

How to Order :

MODEL FTMB-ABS-XX D - XX - XX X				
NO. OF COUPLERS	ADAPTER	MODE	CONNECTOR	POLISH
01-24	D : Duplex	SM : Single Mode M1 : Multi-Mode OM1 M2 : Multi-Mode OM2 M3 : Multi-Mode OM3 M4 : Multi-Mode OM4	1) SC 2) LC 3) FC 4) ST	A : APC U : UPC

Remember to State :

1) Number of Core(s) 2) Type of Coupler 3) Mode of fiber