



Features

- Standard user interface, be made of high impact plastic
- Easy operation and maintenance
- Can accommodate 1x8 or 1x4 PLC splitter
- Anti-UV, Ultra Violet resistant and rainfall resistant
- Wall and pole mountable
- 2 inlet ports, 2 outlet ports for ordinary cable or drop cable

Outdoor ABS Fiber Terminal Box FTMB-ABS Series



Specification	FTMB-ABS-24D
For Number of Couplers	Up to 24
Dimension	Outer: 380 x 305 x 130 mm
	Inner: 360 x 250 x 100 mm
Max Capacity	48 Cores
Operating Temperature	-40°C~+55°C
Atmospheric Pressure	62Kpa~106kpa
Material	ABS
Installation	Wall-mounting or pole-mounting
Application	Local Area Network, CATV Network, FTx System, Wide Area Network, Test Instruments

How to Order :

MODEL	FTMB-ABS-	XX	D	-	XX	-	XX	X
No. Of Couplers	Adapter	MODE	CONNECTOR	POLISH				
I-24	D : Duplex	SM : Single Mode MM : Multi-mode	1) SC 2) LC 3) FC 4) ST	A : APC P : PC U : UPC				

Remember to State :

1) Number of Core(s) 2) Type of Coupler 3) Mode of fiber

Specifications