



Features

- Stretch formed aluminum reflector with high precision
- Well in anti-corrosion
- Excellent in stability
- Accurate in adjustment

Specifications

Model		N860T-AE	N860T-B
Forward Path	Receive Optical Power	-8 ~ +2 dBm	-8 ~ +2 dBm
	Optical Wavelength	1100 ~ 1600 nm	1100 ~ 1600 nm
	Optical Connector Type	FC / APC, SC / APC (Optional)	FC / APC, SC / APC (Optional)
	Optical Fiber Type	Single Mode	Single Mode
	Optical Return Loss	> 55 dB	> 55 dB
	Frequency Range	47 ~ 862 MHz	47 ~ 862 MHz
	Flatness in Band	± 0.75 dB	± 0.75 dB
	Rated Output Level	≥ 108 dBμV (CTB > 60 dB, CSO > 60 dB)	≥ 108 dBμV (CTB > 60 dB, CSO > 60 dB)
	Output Return Loss	≥ 16 dB	≥ 16 dB
	Output Connector	F type	F type
Return Path	Output Impedance	75 Ω	75 Ω
	Frequency Range	---	5 ~ 42 MHz
	Optical Output Level	---	1 mW
	Optical Wavelength	---	1310 nm
	Optical Connector Type	---	SC / APC, FC / APC
	Optical Return Loss	---	≥ 55 dB
General	Power Voltage	AC 220V/50Hz / AC37 ~ 60V/50Hz (Optional)	AC 220V/50Hz / AC 37 ~ 60V/50Hz (Optional)
	Operation Temperature	-20 °C ~ +55 °C	-20 °C ~ +55 °C
	Relative Humidity	Max 95 % non-condensing	Max 95 % non-condensing
	Consumption	≤ 12 W	≤ 12 W
	Dimension (L x W x H)	215 x 165 x 80 mm	215 x 165 x 80 mm

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.