



Features

- Duplex LC receptacle optical interface compliant
- Receiver loss of signal output
- International Class 1 laser safety
- Application: Gigabit ethernet, switch to switch interface,
- Gigabit fiber Channel, switched backplane applications
- Standards: Compliant RoHS

Specifications

Model	FTRM-SFP-20KM
Data Rate (Optical)	1.25Gb
Fiber Type	SMF (1310 nm)
Distance	20km
Optical Interface	LC
Operating Temperature	-10°C~70°C
DDMI	Yes

Model	FTRM-SFP-10KM
Data Rate (Optical)	10G
Fiber Type	SMF (1310 nm)
Distance	10km
Optical Interface	LC
Operating Temperature	-10°C~70°C
DDMI	Yes

Model	FTRM-SFP-550M
Data Rate (Optical)	1.25Gb
Fiber Type	MMF (850 nm)
Distance	550M
Optical Interface	LC
Operating Temperature	-10°C~70°C
DDMI	Yes

Model	FTRM-SFP-300M
Data Rate (Optical)	10G
Fiber Type	MMF (850 nm)
Distance	300M
Optical Interface	LC
Operating Temperature	-10°C~70°C
DDMI	Yes

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.