
















Features

- Easy to install
- Cost effective
- High quality

Optical Accessories

Specifications

<p>Single Mode (SC) Coupler</p>  <p>Coupler: UPC/SX, UPC/DX Insertion loss: 0.2dB Durability: 0.2dB</p>	<p>Single Mode (LC) Coupler</p>  <p>Coupler: UPC/DX, UPC/QX Insertion loss: 0.2dB Durability: 0.2dB</p>	<p>FC Coupler</p>  <p>Coupler: UPC/SX Insertion loss: 0.2dB Durability: 0.2dB</p>
<p>Single Mode APC (SC) Coupler</p>  <p>Coupler: APC/SX, APC/DX Insertion loss: 0.2dB Durability: 0.2dB</p>	<p>Multimode (LC) Coupler</p>  <p>Coupler: UPC/DX, UPC/QX Insertion loss: 0.2dB Durability: 0.2dB</p>	<p>Fusion Splice Protection Sleeve</p>  <p>60mm, Steel core Ø1.0mm 40mm, Steel core Ø1.0mm 25mm, Steel core Ø1.0mm</p>
<p>Alcohol Pump Dispenser Bottle</p>  <p>Material: Plastic 200mL</p>	<p>Drop Cable Stripper</p>  <p>For 3.1 x 2.0mm indoor fiber optic drop cable stripping</p>	<p>High Precision Tri-Hole Stripper</p>  <p>Model: CS-02-B Size: 162mm, Weight: 106g Available for: 125µm, 250µm, 900µm</p>
<p>COMWAY High Precision Fiber Cleaver</p>  <p>Model: C108 Applicable fibers: Single mode or Multimode Provides approximately 48,000 cleaves 24 Position Rotatable and Replicable Blade Dimensions: 62 x 60 x 60mm</p>	<p>Visual Fault Locator</p>  <p>Model: FLL-01 Laser safety rating: Class III A Wavelength: 650nm ± 20nm Output power: 1mW Distance: <5km</p>	
<p>Fiber Cassette</p>  <p>Applicable fibers: Single mode or Multimode Ports: 24 Ports</p>	<p>Optical Fiber Meter</p>  <p>Model: FOPM-850/1625 Applicable fibers: Single mode or Multimode Working wavelength: 850-1625nm Connector: FC / SC Size: 190 x 100 x 48mm</p>	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.