



Features

- Power limited controls
- Single line telephone
- Security systems
- LSZH Jacket option available

Control Cable



Specifications

Model		7024	7028	8723	8761
Conductor	Material	TC	TC	TC	TC
	Cores	4	8	2x2	2
	Max Resistance(20°C)	80Ω/km	80Ω/km	52Ω/km	52Ω/km
	Construction(No./mm)	7/0.2mm	7/0.2mm	7/0.25mm	7/0.25mm
Insulation	Insulation	PVC	PVC	PVC	PVC
	Insulation Dielectric	1.1mm±0.1mm	1.1mm±0.1mm	1.2mm±0.1mm	2.1mm±0.1mm
	Insulation Color	White & Black & Orange & Red	White & Black & Orange & Red & Blue & Green & Yellow & Brown	White & Black & Green & Red	White & Black
Shield	AL Foil	/	/	AL Foil	AL Foil
	Drain wire(No./mm)	/	/	7/0.2mmTC	7/0.25mmTC
Jacket	Jacket Material	PVC	PVC	PVC	PVC
	Jacket Color	White	White	Grey	Grey
	Jacket Thickness	0.6mm±0.05mm	0.65mm±0.05mm	0.7mm±0.05mm	0.85mm±0.05mm
	Jacket O.D	4.1 mm±0.2mm	5.1mm±0.2mm	5.2 mm±0.2mm	5.4 mm±0.2mm
Operation Temperature		-20°C To +60°C	-20°C To +60°C	-20°C To +60°C	-20°C To +60°C
Suitable for		Indoor	Indoor	Indoor	Indoor
Diameter	100 Yards	Φ220x66mm	---	---	---
	200 Yards	Φ220x111mm	Φ220x168mm	Φ220x168mm	Φ220x196mm
Weight	100 Yards	2.2kg	---	---	---
	200 Yards	4.1kg	7.07kg	7.34kg	5.91kg
Construction					

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.