



Features

- Supreme quality
- Intercom / PA systems
- Sound / Audio systems
- LSZH Jacket option available



Specifications

Model		1625	1810	2512
Conductor	Material	TC	BC	BC
	Cores	2	2	2
	Max Resistance (20°C)	24.5 Ω/km	125 Ω/km	63 Ω/km
	Construction (No./mm)	16 / 0.25 mm	18 / 0.1 mm	25 / 0.12 mm + 1 Tinsel copper
Insulation	Insulation	PE	PE	PVC
	Insulation Dielectric	2.2 mm ± 0.1 mm	1.05 mm ± 0.1 mm	1.7 mm ± 0.1 mm
	Insulation Color	White & Transparent	White & Orange	Red & White
Filler	Material	/	Cotton Yarn & Cotton paper	Cotton Yarn
Shield	AL Foil	AL Foil	/	AL Foil
	Spiral (No./mm)	/	71 / 0.1 mm TC	96 / 0.01 mm BC
	Drain wire (No./mm)	10 / 0.25 TC	/	/
Jacket	Jacket Material	PVC	PVC	PVC
	Jacket Color	Grey	Black	Black
	Jacket Thickness	0.65 mm	1.0 mm	1.1 mm
	Jacket O.D	5.5 mm ± 0.2 mm	4.5 mm ± 0.2 mm	6.5 mm ± 0.2 mm
Operation Temperature		-20 °C ~ +60 °C	-20 °C ~ +60 °C	-20 °C ~ +60 °C
Length		200 Yards	100 Yards	100 Yards
Construction				

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.