








Features

- Intercom / PA systems
- Sound / Audio systems
- LSZH Jacket option available



Specifications

Model		1612	1920	1920 LSZH	4215	2008
Conductor	Material	BC	TC	TC	BC	BC
	Cores	2	2	2	2	2
	Max Resistance(20°C)	96 Ω/km	31 Ω/km	31 Ω /km	25 Ω/km	19 Ω/km
	Construction(No./mm)	16 / 0.12 mm	19 / 0.2 mm	19 / 0.2mm	42 / 0.15mm	200 / 0.08mm
Insulation	Insulation	PE	PVC	PE	PVC	PE
	Insulation Dielectric	1.2mm ± 0.02	2.0 mm ± 0.1 mm	2.0 mm ± 0.1 mm	2.9 x 5.8 mm ± 0.1mm	1.8 mm ± 0.1 mm
	Insulation Color	White & Orange	White & Black	White & Transparent	Red & Black	Transparent
Shield	AL Foil	AL Foil	/	/	/	/
	Drain wire(No./mm)	25/0.12mmTC	/	/	/	/
Jacket	Jacket Material	PVC	PVC	LSZH	/	PVC
	Jacket Color	Grey	Grey	Orange	/	Transparent
	Jacket Thickness	0.38mm ± 0.02mm	0.9 mm ± 0.05 mm	0.9 mm ± 0.05 mm	/	1.2mm
	Jacket O.D	3.1mm ± 0.05mm	5.8 mm ± 0.2 mm	5.8 mm ± 0.2 mm	/	4.2X8.4mm±0.2mm
Operation Temperature		-15°C ~ +65°C	-20 °C ~ +60 °C	-20 °C ~ +60 °C	-20 °C ~ +60 °C	-20°C ~ +60°C
Length		100 Yards	100 Yards / 200 Yards / 300M	300 M	100 Yards	100 Yards
Construction						

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.