



Features

- Intercom / PA systems
- Sound / Audio systems
- LSZH Jacket option available

Speaker Cable



Specifications

Model		1920	1920 LSZH	4215	2008
Conductor	Material	TC	TC	BC	BC
	Cores	2	2	2	2
	Max Resistance(20°C)	31Ω/km	31Ω/km	25Ω/km	19Ω/km
	Construction(No./mm)	19/0.21mm	19/0.21mm	42/0.15mm	200/0.08mm
Insulation	Insulation	PVC	PE	PVC	PE
	Insulation Dielectric	2.0mm±0.1mm	2.0mm±0.1mm	2.9x5.8mm±0.1mm	1.8mm±0.1mm
	Insulation Color	White & Black	White & Transparent	Red & Black	Transparent
Shield	AL Foil	/	/	/	/
	Drain wire(No./mm)	/	/	/	/
Jacket	Jacket Material	PVC	LSZH	/	PVC
	Jacket Color	Grey	Orange	/	Transparent
	Jacket Thickness	0.9mm±0.05mm	0.9mm±0.05mm	/	1.2mm
	Jacket O.D	5.8 mm±0.2mm	5.8 mm±0.2mm	/	4.2X8.4mm±0.2mm
Operation Temperature		-20°C To +60°C	-20°C To +60°C	-20°C To +60°C	-20°C To +60°C
Suitable for		Indoor	Indoor	Indoor	Indoor
Diameter	100 Yards	---	---	Φ220 x 61mm	---
	200 Yards	Φ220x200mm	Φ225x204mm	---	---
Weight	100 Yards	---	---	2.95Kg	---
	200 Yards	7.6kg	8.04kg	---	---
Construction					

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.