



## Features

- Supports output resolutions up to 1080 60p
- Easy to use color LCD panel and 6 key buttons
- Small size and Light weight
- Support wall-mount type
- Good ventilation for the device
- Install multiple units onto your TV system
- Support DTMB / DVB-T

## Specifications

| Model          |                | DMODHM2           |                                                    |
|----------------|----------------|-------------------|----------------------------------------------------|
| Standard       | DVB-T Standard | Bandwidth         | 6M, 7M, 8M                                         |
|                |                | Constellation     | QPSK, 16QAM, 64QAM                                 |
|                |                | Code rate         | 1/2, 2/3, 3/4, 5/6, 7/8                            |
|                |                | Guard interval    | 1/4, 1/8, 1/16, 1/32                               |
|                |                | FFT               | 2K, 8K                                             |
| Encoding Video | DTMB Standard  | Bandwidth         | 8M                                                 |
|                |                | Constellation     | GB20600-2006                                       |
|                |                | Encoding          | MPEG4 AVC/H.264                                    |
|                |                | Interface         | HDMIx1                                             |
|                |                | Resolution Input  | 720@50p, 720@60p, 1080@50i/p, 1080@60i/p           |
| Encoding Audio |                | Resolution Output | Max.1080@60p                                       |
|                |                | Bit rate          | Max.25Mbps                                         |
|                |                | Encoding          | MPEG-1 Layer2, AAC                                 |
| System         |                | Sample rate       | 48KHz                                              |
|                |                | Management        | LCD + Control buttons                              |
|                |                | Language          | English                                            |
|                |                | Upgrade           | USB                                                |
| Modulator      |                | Basic             | Standard/CH Number/LCN/CH Name/FHD Output/RF Atten |
|                |                | MER               | Typ. 35dB                                          |
|                |                | RF range          | 100-950MHz, 1KHz step                              |
| General        |                | RF output level   | 100dBμV(25dB Attenuation)                          |
|                |                | Power supply      | 12V1A                                              |
|                |                | Dimensions        | 128 x 77 x 28mm                                    |
|                |                | Weight            | 260g                                               |

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.