



EAD-225RV

2 Megapixel full HD with IR AHD Dome Camera

Features

- Outdoor dome camera
- 24 IR LEDs, 25M
- Vari-focal lens (2.8mm-12mm)
- Approx 140mm diameter
- Aluminum housing
- In-line control unit



IR Coverage



DWDR



ICR Day & Night



DNR



Full HD



S/N Ratio





Aluminum Housing

Specifications

Model: EAD-225RV

Video	Signal System	PAL / NTSC
	Imaging Sensor	2MP CMOS Imaging Sensor
	Pixels	1920 x 1080
	Resolution	1080P
	Lens Type	2.8mm ~ 12mm
	Minimum Illumination	Color 0.01 Lux B/W 0 Lux (IR LED ON)
	Day & Night	Yes
	Sync. System	Internal
	S/N Ratio / DWDR	Digital >50dB
	Video Output Signal	1Vp-p, 75Ω
	IR LED	24 EA
	IR Distance	Approx. 25M
Operational	Backlight Compensation	BLC / HSBLCL / OFF
	DNR	2D + 3D - DNR
	Electronic Shutter Speed	Auto, 1/50 - 1/500000s
	White Balance	AWB, ATW, Indoor, Outdoor, Manual
	Privacy Zone Masking	4 Zones
	Motion Detection	Yes
	Digital Effect	Off / V-Flip / Mirror / Rotate
	Multi OSD Language	ENG, CHN
General	Communication	Coaxial Communication (UTC)
	Power Source	DC12V
	Power Consumption	2.0W
	Operating Temperature / Humidity	-10°C ~ 50°C / < 90%
	Storage Temperature / Humidity	-40°C ~ +60°C / 20 ~ 95%
General	Dimension	110 x Ø140mm

DIMENSION (Unit: mm)



In-line control unit

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.