



## EIR-H1032 32 Channel NVR with 2-SATA Bays

### Features

- Support HDMI 4K Output VGA HD Output
- Support ONVIF, Access Third Party
- Support Web, CMS, Center Platform Management Software
- Support multiple cloud technology, network penetration, Alarm Information Pushed to Your Phone and Other Functions
- Support Multiple Network Services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.)

### Specifications

Model: EIR-H1032		
System & interface	Main Processor	Hi3536C
	Operating System	Embedded Linux
	System Resources	Simultaneous multi-channel real-time recording, Playback, Network operation, USB backup
	Operator Interface	16-bit true color graphic menu operation interface, Support mouse operation
Video & Audio	Preview	1 / 4 / 9 / 16 / 32
	Video Input (IP)	32x4K / 32x5M / 32x1080P
	Access Bandwidth	300 Mbps
	Forwarding Bandwidth	240 Mbps
	Video Compression	H.265 / H.264
	Display Quality	4K
	Playback Quality	4K / 5M / 1080P
	Decode	1x4K / 2x5M / 4x1080P
	Motion Detection	Support (Depend on camera)
	Audio Compression	G.711A
	Intercom	Support
Record & Playback	Recording Mode	Manual > Alarm > Dynamic Detection > Timing
	Local Playback	1x4K / 2x5M / 4x1080P
	Search Mode	Search by Time / Calendar / Event / Channel
	Record Storage	HDD, Network
	Backup Mode	Network backup, USB hard disk, USB burner, SATA burner
External Interface	Video Output	1ch VGA, 1ch HDMI HD output
	Audio I/O	1/1
	Alarm I/O	0/0
	Network Interface	1xRJ45 10M/100M/1000M Adaptive Ethernet port
	USB Interface	2 x USB2.0 ports
	HDD	2 SATA (Up to 8TB for each disk)
	ESATA	No
General	Serial Interface	No
	ONVIF	Support
	Power Supply	12V / 4A
	Power Consumption	<10W (Without HDD)
	Work Environment	Temperature
		Humidity
		Atm

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.