



Features


- Comply with ANSI/EIA, RS-310-D; IEC297-2; DIN41491: PART 1; DIN41491: PART 7; GB/T3047.2-92 standard
- Door lockable
- LC & SC adapter available
- Supplied with accessories

Specifications

Model	FTMB-METAL-4D Series	FTMB-METAL-8D-Series	FTMB-METAL-12D-Series
For Number of Coupler	4	8	12
Capacity	LC	4 Capacity / 8 cores (Max.)	12 Capacity / 24 cores (Max.)
	SC	4 Capacity / 4 cores (Max.)	12 Capacity / 12 cores (Max.)
	ST	4 Capacity / 4 cores (Max.)	12 Capacity / 12 cores (Max.)
	FC	4 Capacity / 4 cores (Max.)	12 Capacity / 12 cores (Max.)
Dimension	140 x 105 x 28mm	200 x 148 x 30 mm	245 x 200 x 48 mm
Number of Door	1	1	1

Model	FTMB-METAL-24D Series	FTMB-METAL-48D Series
For Number of Couplers	24	48
Capacity	LC	24 Capacity / 48 cores (Max.)
	SC	24 Capacity / 24 cores (Max.)
	ST	24 Capacity / 24 cores (Max.)
	FC	24 Capacity / 24 cores (Max.)
Dimension	376 x 355 x 115 mm	376 x 355 x 115 mm
Number of Door	2	2

How to Order :



Remember to State :

- 1) Number of Core(s) 2) Type of Coupler 3) Mode of fiber