




### Features

- Use for Video Surveillance and Security applications
- HDMI, VGA, BNC and Audio input
- Support 3D comb filter and 3D de-interlace high quality image
- Auto-ON when video source is detected
- LED panel with extra wide viewing angle
- CE certified
- HDMI certified

### Specifications

Model		MAX22	MAX24	MAX32	
Panel	Screen Size	21.5"	23.8"	31.5"	
	Brightness	300 cd/m2	300 cd/m2	300 cd/m2	
	Contrast	1000:1	1000:1	1000:1	
	Pixel Pitch (mm)	0.248 (H) x 0.248(V)	0.2745 (H) x 0.2745(V)	0.36375 (H) x 0.36375(V) mm	
	Resolution (H x V)	1920 x 1080	1920 x 1080	1920 x 1080	
	Aspect Ratio	16:9	16:9	16:9	
	View Angles	H 170°/V 160°	H 178°/V 178°	H 178°/V 178°	
	Response Time	5ms	5ms	5ms	
	Display Colors	16.7M colors	16.7M colors	16.7M colors	
Input & Output	Display Frequency	1920 x 1080 /75Hz	1920 x 1080 /75Hz	1920 x 1080 /75Hz	
	Input	VGA x1, HDMI x1, BNC x1, Audio x1	VGA x1, HDMI x1, BNC x1, Audio x1	VGA x1, HDMI x1, BNC x1, Audio x1	
	Output	BNC, Speaker:3Wx4Ω	BNC, Speaker:3Wx4Ω	BNC, Speaker:3Wx4Ω	
General	Consumption (Max)	On: ≤30W ; Standby≤0.5W	On: ≤30W ; Standby≤0.5W	On: ≤35W ; Standby≤0.6W	
	Power	100-240V~ 50/60HZ	100-240V~ 50/60HZ	100-240V~ 50/60HZ	
	Power Mode	Power on : BLUE (LED Light ), Power saving : RED (LED Light)	Power on : BLUE (LED Light ), Power saving : RED (LED Light)	Power on : BLUE (LED Light ), Power saving : RED (LED Light)	
	Humidity	20% ~ 85%, non-condensing	20% ~ 85%, non-condensing	20% ~ 85%, non-condensing	
	Temperature	0°C~55°C	0°C~55°C	0°C~55°C	
	Dimension	A	509 mm	542 mm	715 mm
		B	306 mm	322 mm	421 mm
		C	373 mm	402 mm	520 mm
		D	48 mm	45 mm	64 mm
		E	200 mm	179 mm	210 mm
Weight	3.2 kg	4.25 kg	7.15 kg		
VESA	100 x 100 mm	100 x 100 mm	75 x75mm		

DIMENSION (Unit: mm)



ACCESSORIES: TV-WM



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.