



Features

- UL grade available, contact us for details
- ISO9001 Certified Manufacturing Plant
- Other options are available, please ask our sales representative for detail



Specifications

Model		CU5890BV	
Construction	Inner Conductor	Stranded Copper Wire	
	Braid Coverage	90%	
	Center Conductor	19 x 0.18 mm	
	Solid PE Insulation	2.95 mm	
	TIN - Copper Braiding	16 x 6 x 0.12 mm	
	PVC - Jacket	5.00 mm	
Electric Specifications	Inner Conductor Resistance	38 Ω / km	
	Outer Conductor Resistance	20 Ω / km	
	Loop Resistance	53	
	Nominal Capacitance	10 pF /m	
	Impedance	50 Ω±2	
	Propagation Velocity Ratio	66% Nominal	
	Application Temperature	- 40°C ~ +75°C	
Packing	Length	100 Yards	200 Yards
	Size	26 x 10 x 7.2 cm	26 x 10 x 13 cm
	Reels in a Carton	4 Reels in a Carton	2 Reels in a Carton
	Gross Weight	16 kg	
	Net Weight	15 kg	

Frequency MHz	50	100	200	550	750	800	1000
Attenuation Nominal dB/100m	10.30	14.78	21.42	38.26	46.12	48.07	54.96

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.