



Features

- Dual bonding
- Application temperature - 20°C ~ +60°C
- Flooding compound available
- Messenger wire with different breaking strength options
- UL grade available, contact us for details
- LSZH option available for these IEC standards
- IEC61034-2:2005, IEC60754-1:2011, IEC60332-1-2:2004
- ISO9001 Certified Manufacturing Plant
- Other options are available, please ask our sales representative for detail

Coaxial Cable RG6



Armour Available

Specifications

Model		CS640BV	CS660BV	CS690BV	CS660BVT
Construction	Inner Conductor	Copper Clad Steel 20% conductivity	Copper Clad Steel 20% conductivity	Copper Clad Steel 21% conductivity	Copper Clad Steel 21% conductivity
	Braid Coverage, Aluminum Wire	40%	60%	90%	60%
	Center Conductor Diameter (mm)	1.02 ± 0.01	1.02 ± 0.01	1.02 ± 0.01	1.02 ± 0.01
	Bonded Foam PE Dielectric (mm)	4.62 ± 0.10	4.62 ± 0.10	4.57 ± 0.10	4.57 ± 0.10
	Sealed Tape (mm)	4.75 ± 0.10 (AP)	4.75 ± 0.10 (AP)	4.78 ± 0.10 (APA)	4.78 ± 0.10 (APA)
	Aluminum Braiding (mm)	5.16 (16 x 3 x 0.12 mm)	5.16 (16 x 5 x 0.12 mm)	5.38 (16 x 8 x 0.16 mm)	5.38 (16 x 4 x 0.16 mm)
	Unsealed Tape (mm)	---	---	---	5.56
Electric Specifications	PVC Jacket (mm)	6.80 ± 0.15	6.80 ± 0.15	6.91 ± 0.15	7.06 ± 0.15
	Nominal DC Resistance Inner Conductor	105 Ω / km	105 Ω / km	100 Ω / km	100 Ω / km
	Nominal DC Resistance Outer Conductor	70 Ω / km	49.5 Ω / km	18.56 Ω / km	21.35 Ω / km
	Nominal DC Resistance Loop	175 Ω / km	144.5 Ω / km	118.56 Ω / km	121.35 Ω / km
	Nominal Capacitance	53.0 pF / m	53.0 pF / m	53.0 pF / m	54.0 pF / m
	Capacitance Impedance	75 ± 3 Ω	75 ± 2 Ω	75 ± 2 Ω	75 ± 2 Ω
Packing	Nominal Velocity of Propagation	85% nominal	85% nominal	85% nominal	85% nominal
	100-Yards Coil/ Carton (6 Coils, 5 Boxes)	28 x 28 x 55 cm	30 x 30 x 53 cm	---	30 x 30 x 53 cm
	Weight (Net / Gross, kg)	22 / 23	23 / 24	---	23 / 24
	1000-Feet Reel Size (cm)	---	32 x 15 x 30	32 x 15 x 30	---
	Weight (Net / Gross, kg)	---	12 / 13	15 / 16	---

- Steel messenger wire 1.30 mm models are available with the above spec: **CS640BVM, CS660BVM, CS690BVM**
- Flooding compound models are available with the above spec: **CS640BVMF, CS660BVMF, CS690BVMF**
- LSZH Jacket option available
- Armour type available

Frequency MHz	5	55	211	250	270	300	330	400	450	500	550	600	750	870	1000	1500	2000	2050	2200
Attenuation Nominal (±0.5)dB/100m	1.90	4.82	9.25	10.11	10.54	11.15	11.74	13.02	13.87	14.67	15.46	16.23	18.41	20.05	21.29	27.10	29.71	30.06	30.24

- Attenuation increases with increasing temperature and decreases with decreasing temperature at the rate of 0.18%/°C
- DC resistance changes at the rate of 0.393%/°C
- All values are nominal figures

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.